



SELF-ADHESIVE LOOP LABEL FOR WAREHOUSE LOGISTICS

PRESSURETAC TT 80

satin 7753, 85 g/m²

Linerless, self-adhesive, satin-finished paper for manual labelling as a loop tag.

PRESSURETAC TT 80 is a satin-finished, FSC® certified 80g paper with reverse coating that only sticks to itself. There is no need for waste-intensive silicone paper, making PRESSURETAC an environmentally friendly alternative to conventional self-adhesive paper.

PRESSURETAC TT 80 is supplied in roll format and can be used immediately. No punching or perforation is required when the thermal printer has a cutter or perforation blade fitted. Text or variable information is thermal transfer printed. The paper is optimised for Flexo pre-printing; it's possible to partially print the adhesive layer too.

Advantages

- Only sticks together coating to coating
- Reduced risk of accidents during processing as no silicone paper to discard
- Can be removed without any hint of residue – no cleaning required on wire mesh crates, cages, trays, trolleys or tensioning straps
- Ready-to-use for the final application – no punching / perforation required
- Variable material thickness – appropriate for manual and mechanical application
- Environmentally friendly as FSC® certified and without silicone paper (linerless)
- Suitable for use in all storage rooms - at temperatures of -20°C to +30°C
- Can be recycled with paper products (according to category II of the PTS (Papiertechnische Stiftung) test method RH 021/97)



Technologies



Properties



- Sticks to itself
- Residue-free removal

General tips

For quality reasons PRESSURETAC should be stored originally packed. Storage & converting conditions of 23±5°C and 50±10% rel. humidity are recommended.

PRESSURETAC TT 80 is recyclable according to category II of the PTS (Papiertechnische Stiftung) test method RH 021/97

Physical data

Name	Value	Tolerance	Norm
Weight [g/m ²]	85	±10	ISO 536
Thickness (paper) [µm]	80	±10	ISO 534
Application temperature [°C]	-5 bis +30		

Durability

The product can be stored original packed for at least 9 months under these conditions.

Printing instructions

Printing and processing recommendations are available for download.