EXHIBITION STAND CONSTRUCTION / POS / EVENTS

ROLL-UP FILM PLUS 205 SB SATIN

satin 3598, 205 µm

Polypropylene/polyester composite material with matt, silver back for roll-up displays

Roll-Up Film Plus 205 SB Satin is suitable for the creation of high quality roll-up and display graphics using solvent, latex and UV inks. The satin finish guarantees robust and scratch resistant prints, characterised by high colour brilliance, saturation and image sharpness. The tear resistant polypropylene/polyester composite enables problem free processing, while offering a high opacity due to the matt, silver back. The attractive price-performance ratio makes the product especially suitable for high volume projects used short to mid-term. An increase in general productivity is possible thanks to the good printing results achieved with fast print mode (HP Latex up to 6 pass).

Technologies

SOL LAT UV

Properties

Advantages

- Brilliant colour reproduction
- Matt, silver back for high opacity
- Good flatness
- Tear resistant
- Scratch resistant
- Anti-reflective, satin surface
- Higher productivity thanks to good results with fast print modes (HP latex to up 6 pass)
- PVC free

General tips

- In general, we strongly recommend that all prints are left 24 hours to transpire.
- The product should be stored in original packaging at a room temperature of 15 – 25°C and at a relative humidity of 40 – 60%.

Physical data

Name	Value	Norm
Thickness (film) [µm]	205	ISO 4593
Weight [g/m²]	165	ISO 536
Whiteness, CIE D65/2°	109	ISO 11476
Opacity [%]	99.8	ISO 2471
Gloss (60°)	8.4	ISO 2813